

AN/PVS-26 UNIVERSAL NIGHT SIGHT™ (LRLP) GENERATION 3 PINNACLE®

The AN/PVS-26 PINNACLE® is designed for long range, low profile night time applications and features a 120mm refractive telephoto lens design. The PVS-26 can utilize either a single battery, either AA or a DL123 type.

When using a DL123 type battery, the PVS-26 LRLP power system is designed to allow it to operate for several hours on what would be considered an otherwise "dead" DL123 battery discarded from a flashlight or other illumination device. The power system even allows for the battery to be changed while the shooter remains in shooting position, making the PVS-26 a very effective scope for all types of sniper applications.



Standard Accessories (Included):

- Shroud wrap
- Lens cover
- Base adjustment Wrenches
- Lens cleaning kit
- KAC Quick attached detach 1913 mount – this is the mount spec for the AN/PVS-22
- AA battery
- Soft Carry Case
- Technical Manual

PART #: MVP-26328

Product Features:

- The in-line UNS® LRLP weapon sight adds night capability to the existing rifle & day sight.
- The UNS® LRLP is universal. It fits most fielded rifles & day sights.
- Cheek weld, eye relief, & bullet impact, are unchanged when the UNS® LRLP is clipped on the rifle.



Human Detection Ranges (Approx):

- Starlight: 800 or > meters
- ¼ Moonlight: 1000 or > meters

MOROVISION NIGHT VISION, INC.
23382 Mill Creek Drive, Suite D-115
Laguna Hills, CA 92653

By Phone: Toll Free 1-800-424-8222 or 949-581-9988
By Fax: 949-581-1133
Email: info@morovision.com
Website: <http://www.morovision.com>

EXPORT NOTICE:

Export of this product is regulated by the U.S. Department of State in accordance with guidelines of "International Traffic in Arms Regulations (ITAR)" per Title 22, Code of Federal Regulations, Parts 120-130.

This data sheet is approved for unlimited release. Specifications subject to change without notice.

SPECIFICATIONS: MVP-26328

Intensifier Tube	Generation	3 U.S. (ITT PINNACLE®)
	Resolution	64 lp/mm (Min)
Optics	Magnification	1x (Unity)
	Field of View	9°
	Objective Lens f/number / focal length	120mm Refractive Telephoto
	Range of Focus	20 meters to infinity
	Boresight Accuracy:	within .5 MOA
	Boresight Retention:	.5 MOA or Better over 300 rounds
	Boresight Adjustment:	None Required
Power	Power Source	One (1) AA batteries or (1) DL123 type
	Operating Time	55 hrs @ room temperature
Environmental Characteristics	Storage Temperature	-6°F to +160°C
	Operating Temperature	-6°F to +113°C
Physical Characteristics	Size:	
	Length	9.5"
	Width	3.0" OD
	Weight:	
	w/batteries & lens cap	3 lbs 6 oz's
	Finish:	Black, Matte Finish, Corrosion Resistant
Mount:	KAC 26597 for Quick Attach/Detach to MIL-STD-1913 Rail or equivalent mounting surface	
Warranty	System	One (1) year
Features	Water Resistant	3 ft for 4 hrs.
	Weapons Certification:	Up to and including .50 caliber rifles.

MOROVISION NIGHT VISION, INC.
23382 Mill Creek Drive, Suite D-115
Laguna Hills, CA 92653

By Phone: Toll Free 1-800-424-8222 or 949-581-9988
By Fax: 949-581-1133
Email: info@morovision.com
Website: <http://www.morovision.com>

EXPORT NOTICE:

Export of this product is regulated by the U.S. Department of State in accordance with guidelines of "International Traffic in Arms Regulations (ITAR)" per Title 22, Code of Federal Regulations, Parts 120-130.

This data sheet is approved for unlimited release. Specifications subject to change without notice.