

Thermal-Eye™ X-200xp Thermal Imager

The Thermal-Eye™ X200xp has advanced significantly beyond its [X100xp](#) predecessor, which has performed with accolades in both Afghanistan and Iraq. This new unit offers 50% greater stand-off-range than the previous generation's unit and can detect human activity at up to 450 meters/1,500 feet (about the length of four football fields). The X200xp also has improved image processing for best-in-class image quality. The unit's sophisticated image processing provides greater scene detail and improved clarity and sharpness. The advanced technology also offers improved vision in challenging field conditions like dust, smoke and complete darkness, all while preventing a blooming effect from nearby lights common in image intensification cameras. The 30-hertz, 30- μ m detector ensures not only a fast turn-on time, but also real-time video imaging.

Features:

- Developed with advanced amorphous silicon microbolometer technology.
- Rugged design with integral rubber eye cup can survive accidental drops and underwater submersion to 9 feet.
- Pocket-sized, weighing only 13 ounces.
- Detects human activity from over 300 meters away.
- Sealed cover for enclosing video and power jacks
- Operates for 3 hours on 2 commercial AA alkaline batteries.

Standard Equipment:

- Thermal-Eye™ X200xp Thermal Imaging Camera
- Hard Protective Case
- 2 AA Alkaline Batteries
- Neck Strap & Wrist Strap
- Lens Cover
- Lens Cleaning Cloth
- Operator's Manual
- 1 Year Warranty



PART #: RCP-7070410-0001

Characteristics:

- Provide an officer the ultimate safety and security solution
- Provide an incredibly clear picture of the surrounding scene, up to 1000 feet, through the use of superior imaging software
- 30 hertz 30 μ m detector offers fast turn-on time and real-time video image
- Sophisticated image processing for best-in-class image quality
- Rugged design with integral rubber eyecup can survive accidental drops and underwater submersion to 9 feet
- Pocket-sized, weighing only 13 ounces
- Operates on 2 AA alkaline batteries

MOROVISION NIGHT VISION, INC.
23382 Mill Creek Drive, Suite D-115
Laguna Hills, CA 92653

By Phone: Toll Free 1-800-424-8222 or 949-581-9988
By Fax: 949-581-1133
Email: info@morovision.com
Website: <http://www.morovision.com>

EXPORT NOTICE:

Export of this product is regulated by the U.S. Department of State in accordance with guidelines of "International Traffic in Arms Regulations (ITAR)" per Title 22, Code of Federal Regulations, Parts 120-130.

This data sheet is approved for unlimited release. Specifications subject to change without notice.

MORO VISION NIGHT VISION

LIGHT THE NIGHT™



SPECIFICATIONS: Thermal-Eye™ X200xp RCP 7070410-0001

Focal Plane Array	Type & Material	Amorphous Silicon Microbolometer
	Pixel Count (Resolution)	160 x 120
	Spectral Response	7-14 μm (filter bandwidth)
	Thermal Sensitivity	≤ 50 mK
Thermal Imaging Performance	Startup Time	~ 4 sec
	Detection Range for Human Activity	Up to 1000 Feet (305 meters)
	Contrast / Brightness	Fully Automatic
	Susceptibility to Blinding Visible Light	None
	Infrared Polarity	White = Hot, Black = Cold
Optics	Lens Focal Length	25mm
	Field of View	11° x 8°V
	Minimum Focus Distance	~ 3 ft. (1 meter)
Video	Output Format	Analog NTSC or PAL on rear outlet jack
	Viewfinder Display	Monochrome LCD (320 x 240 pixels)
	Viewfinder Dimming	Integral to power on/off switch
Power	Power Source	Two (2) AA batteries
	Operating Time	~ 2 Hours with alkaline
	Auxiliary Power	12 VDC input on rear outlet jack
Environmental Characteristics	Operating Temperature	-4°F to 140°F (-20°C to 60°C)
	Storage Temperature	-4°F to 176°F (-20°C to 80°C)
	Water & Shock Resistance	Waterproof to 9ft (3m) submersion, buoyant in fresh water Shockproof to 6 ft (2m) drop
	EMC Compliance	FCC Part 15 & CE Mark
Physical Characteristics	Size	5 1/4" L x 4 1/2" W x 2" H (13.4 x 11.4 x 5.1 cm)
	Weight	13 oz (381g), batteries installed
	Eye Cup	Integral to camera body with 2" eye relief

MOROVISION NIGHT VISION, INC.
23382 Mill Creek Drive, Suite D-115
Laguna Hills, CA 92653

By Phone: Toll Free 1-800-424-8222 or 949-581-9988
By Fax: 949-581-1133
Email: info@morovision.com
Website: <http://www.morovision.com>

EXPORT NOTICE:

Export of this product is regulated by the U.S. Department of State in accordance with guidelines of "International Traffic in Arms Regulations (ITAR)" per Title 22, Code of Federal Regulations, Parts 120-130.

This data sheet is approved for unlimited release. Specifications subject to change without notice.